

DH-PFM350-360

Uninterruptible Power Supply(UPS)——Line-interactive



Features

- Wide input voltage range: AC140~290Vac, meet the requirements in different parts for electric network fluctuation.
- Boost and buck AVR for voltage stabilization.
- Off-mode charging, cold start function and full protection.
- Continuous power supply for preventing data loss.
- Compact size.

Technical Specifications

Model	DH-PFM350-360	
Capacity	600VA/360W	
Input		
Rated voltage	110Vac~120Vac or 220Vac~240Vac	
Voltage range	81Vac~145Vac or 140Vac~290Vac	
Rated frequency range	60/50Hz	
Power factor	0.6	
Output		
Voltage	110/120 VAC or 220/230/240 VAC	
AC Voltage Regulation (Batt. Mode)	±10%	
Frequency Range (Batt. Mode)	60Hz or 50Hz±1Hz	
Transfer Time	2-6ms	
Waveform (Batt. Mode)	Simulated sinewave	
Battery		
Battery type & number	12 V/7 Ah x 1	
Typical recharge time	4 hours recover to 90% capacity	
Charging voltage	13.7V±1%	
Indicators		
Battery mode	Green lighting	
AC mode	Green lighting	
Alarm		
Battery mode	Sounding every 10 seconds	
Low battery	Sounding every second	
Overload	Sounding every 0.5 second	
Fault	Continuously sounding	
Protection		
Full protection	Overload, discharge and overcharge protection	
Environmental		
Operating temperature	0°C ~ +40°C (+32°F ~ +104°F)	
Operating humidity	0~90% RH(non-condensing)	
Altitude range	<1000m(3280.84ft)	
Construction		
Color	Black	
Noise level	<40dB	
Dimensions	279mmx101mmx142mm(10.98"x3.98"x5.59")	
Weight	4.25kg(9.37lb)	

Order Information

Туре	Part Number	Description
Power Series	DH-PFM350-360	Uninterruptible Power Supply(UPS)
		_Dahua brand, Line-interactive
	DH-PFM350-900	Uninterruptible Power Supply(UPS)
		_Dahua brand, Line-interactive
	DH-PFM351-900	Uninterruptible Power Supply(UPS)
		_Dahua brand, Smart online

Package Information

- Uninterruptible Power Supply(UPS) DH-PFM350-360 *1
- Installation Instruction *1

